

	<b>AGAS Lubes WLL</b>	Document ID:	<b>AL-IMS-PROD-HFD</b>
	<b>Product Specification</b>	Version:	<b>03</b>
		Date of last tested:	<b>15/04/2021</b>
		Page:	<b>1 of 1</b>
		Information classification:	<b>Public</b>

**Product Name: High Flash Diesel (HFD)**



Sr. No.	Parameters	Test Method	Unit	HFD
1	Appearance	Visual	-	Clear and Bright
2	ASTM Colour	ASTM -D 1500	-	<3.0
3	Density at 15 deg C	ASTM -D 1298	gm/mL	0.85 – 0.87
4	Kinematic Viscosity at 50 deg C	ASTM -D 445	cSt	16- 22
5	Cetane Index	ASTM -D 976	-	55
6	Moisture content	ASTM -D 95	% vol	Nil
7	Sulphur Content, max	ASTM -D 4294	% w/w	0.3
8	Flash point (PMCC), min	ASTM -D 93	Deg. C	100
9	Ash Content	ASTM -D 482	% w/w	Nil
10	Conradson Carbon Residue, max	ASTM -D 189	% w/w	0.1
11	Gross Calorific Value	ASTM -D 4868	kcal/kg	>10000
12	Net Calorific Value	ASTM -D 4868	kcal/kg	>9000