

	<b>AGAS Lubes WLL</b>	Document ID:	<b>AL-IMS-PROD-SN300</b>
	<b>Product Specification</b>	Version:	<b>05</b>
		Date of last tested:	<b>15/01/2023</b>
		Page:	<b>1 of 1</b>
		Information classification:	<b>Public</b>

**Product Name: SN300**



Sr. No.	Parameters	Test Method	Unit	SN-300
1	Appearance	Visual	-	Clear and Bright
2	ASTM Colour	ASTM -D 1500	-	3.5 – 4.0
3	Density at 15 deg C	ASTM -D 1298	gm/mL	0.86 - 0.87
4	Kinematic Viscosity at 40 deg C	ASTM -D 445	cSt	38 – 40
5	Kinematic Viscosity at 100 deg C	ASTM -D 445	cSt	6.0 - 6.5
6	Viscosity Index, Min	ASTM -D 2270	-	100
7	Flash point, Min	ASTM -D 92	Deg. C	200
8	Total Acid Number, mg KOH/g	ASTM -D 664	mgKOH /gm	< 0.05
9	Crackle Test/Moisture	Standard Method	-	Negative
10	Pour Point, max	ASTM -D 97	Deg. C	-6
11	Copper Strip Corrosion, max	ASTM -D 130	-	1A
12	Conradson Carbon Residue	ASTM -D 189	%w/w	<0.5
13	Ash Content	ASTM -D 482	%w/w	0.01
14	Sulphur Content	ASTM -D 4927	%w/w	<0.5